


Oilzone

Oilzone is a high quality anti-fatigue, anti-slip resistant mat perfect for use in areas where oil and chemicals are in frequent use. Made of 100% nitrile rubber, the open cell structure and raised studs, allow fluids and debris to drain through leaving a dry, safe and comfortable work surface. Highly visible orange bevel edges are attached to three sides to provide added safety. Oilzone can be used in both wet or dry environments.

Features

- Typical applications: Perfect for oily machine areas, manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual work stations and custom work platforms.
- Material: 100% nitrile rubber.
- Cleaning: Wash with water and a mild detergent.
 Can use a jet wash if required.
- Sustainability: REACH and RoHS compliant.
- Warranty: Lifetime.



Black with orange bevel edge



For more information about this product or, to place an order click here

Code	Metric	Imperial	Thickness	Weight	Colour
OZ2640	66cm x 102cm	2' × 3'	22mm	8.8kg	Black
OZ3864	97cm x 163cm	3' x 5'	22mm	21kg	Black
OZ310	97cm x 315cm	3' x 10'	22mm	37.2kg	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

Get in touch

+44 (0) 1779 841 899 sales@bluediamond.uk.com www.bluediamond.uk.com



Oilzone

Technical Specification				
Slip resistant:	Raised studs on the surface provide excellent slip resistance in all environments, resistant level 3			
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3			
Wear resistant:	Excellent wear resistant to level 3, suitable for heavy footfall			
Water absorbent:	The design allows liquids to self-drain			
Chemical resistant:	Yes			
Dry area:	area: Yes			
Wet area:	ea: Yes			
Oily and greasy area:	Yes			
Heavy area:	Yes			
Welding area:	Yes			
Wheeled area:	Yes, the ramped edges allow easy moveability for wheeled trolleys or machinery			
Environment:	Suitable for wet or dry, metal work, fluids, oils and chemicals usage			
Flame retardant:	Yes			
Impact resistant:	Yes			
Product testing:	 Abrasion Resistance 1000 3.1% Hardness 33 Shore A Coefficient Friction Dry 0.65 Fire Rating US - Pass Surface Flammability - Pass 			
Sustainability:	 REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) RoHS (Restriction of Hazardous Substances) 			
Cleaning:	Wash with water and a mild detergent. Can use a jet wash if required			