

Rubber Rib Mat Electrical (450v)

The Rib Mat Electrical (450v) is a high quality, non-conductive rubber safety mat, designed to provide insulation and protect workers from electric shocks. Rubber Rib Mat Electrical is fully certified and tested to 11000 volts with a recommended working voltage of 450 volts. The regulation standard is stamped on the reverse at 1m intervals as the image below shows. The fine ribbed surface also offers great anti-slip protection and has an overall thickness of 6mm.

Features

- Typical applications: Perfect solution for live switchboards, lower voltage switchboard applications, generators, electrical equipment and repair workstations.
- Material: Natural rubber.

Warranty: Lifetime.

- Cleaning: Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended.
- Sustainability: REACH compliant. Contributes to a clearer environment by reducing the need to use cleaning chemicals.



Black only, image shows reverse of the mat



For more information about this product or, to place an order **click here**



Code	Metric	Imperial	Thickness	Weight	Туре	Colour
RE691	90cm x 10m	3' x 33'	6mm	80kg	Roll	Black
RE6100	100cm x 10m	3' x 33'	6mm	88kg	Roll	Black
RE6122	120cm x 10m	4' x 33'	6mm	97kg	Roll	Black
RE691C	90cm wide	3' wide - per m	6mm	8kg	Cut length - per m	Black
RE6100C	100cm wide	3' wide - per m	6mm	8.8kg	Cut length - per m	Black
RE6122C	120cm wide	4' wide - per m	6mm	10.6kg	Cut length - per m	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference. v31023

Get in touch

+44 (0) 1779 841 899 sales@bluediamond.uk.com www.bluediamond.uk.com



Rubber Rib Mat Electrical (450v)

Product Data Sheet

Technical Specification					
Slip resistant:	Great slip resistance to level 2				
Anti-fatigue:	Good anti-fatigue properties, resistant to level 1				
Wear resistant:	The fine ribbed surface offers great wear resistance to level 2				
Cut to length:	Yes, mat can be cut to length				
Cut to size:	Yes, mat can be cut to bespoke sizes				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Heavy area:	Yes				
Wheeled area:	Yes, the low profile allows easy access for light weight wheeled traffic				
Environment:	Suitable for indoor use				
Impact resistant:	Yes				
Non-conductive (Electrical):	Yes				
Product testing:	 Fully electrically tested and certified to 11kv, recommended safety working voltage of 450v Tensile strength (N/mm²): 3.5 (ISO 37) Hardness Shore A: +/-5 70° (ISO 7619-1) Density SG (g/cm²): 1.5 (ISO 37) Elongation: 300% (ISO 37) Abrasion resistance (mm³): 180 (ISO 37) Tear strength: 20 (ISO 34-1) 				
Sustainability:	 REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals 				
Temperature resistance:	-20°C to +70°C				
Cleaning:	Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended				