



Chequer Plate Mat Single Bar - 3mm

Chequer Plate Matting is a low-cost surface covering, recommended for applications where safety and slip protection are crucial but without the need for anti-fatigue properties. The diamond-embossed chequer plate surface provides exceptional non-directional grip, making it suitable for workbenches as well as flooring.

This lightweight matting is available in both rolls and cut lengths.

Features

- ◆ **Typical applications:** Perfect for warehouse aisles, industrial walkways, as shelf liners, on workbenches and near machines to prevent objects sliding.
- ◆ **Material:** 100% rubber.
- ◆ **Cleaning:** Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Black only



Suitable for indoor use



For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
CR3122-1	120cm x 10m	4' x 33'	3mm	35kg	Roll	Black
CR3122-1C	120cm wide	4' wide	3mm	3.5kg	Cut length - per m	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

V1.03.24

Get in touch

+44 (0) 1779 841 899
sales@bluediamond.uk.com
www.bluediamond.uk.com

Chequer Plate Mat Single Bar - 3mm

Technical Specification

Slip resistant:	Great slip resistance to level 2
Anti-fatigue:	Good anti-fatigue properties, resistant to level 1
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall
Cut to length:	Yes, mat can be cut to length
Cut to size:	Yes, mat can be cut to bespoke sizes
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users
Dry area:	Yes
Wheeled area:	Yes, the low profile allows easy access for wheeled traffic
Environment:	Suitable for indoor use
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none">◆ Hardness: 85+/-5 shore A - DIN ISO 7619-1◆ Volume weight: 1.82g/cm³ - DIN 53504◆ Tensile strength: Direction 1 - 1690psi/direction 2 - 1940psi ASTM D412-16◆ Elongation at break: 190% - ASTM D3574-17 Test E◆ Puncture resistance - EN388:2016+A1:2028, Clause 6.5◆ Indentation resistance - ASTM F970-17
Sustainability:	<ul style="list-style-type: none">◆ Nature friendly, biodegradable and recyclable◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals
Cleaning:	Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended