

Chevron

Chevron is a high performing entrance mat, the herringbone pattern offers great brushing and wiping action and is the perfect choice for heavy foot traffic areas, such as entranceways and lobbies. The dense vinyl backing also helps to minimise movement of the mat once in place.

Features

- Typical applications: Excellent for schools, offices, commercial establishments, retail and industrial entrances.
- Material: 100% polypropylene.
- Cleaning: Vacuum, extraction clean, or can be hosed off.
- Sustainability: REACH compliant.
- Warranty: Lifetime.



Charcoal only, other colours available on request



For more information about this product or, to place an order click here

| Code | Metric | Imperial | Thickness | Weight | Colour |
|----------|---------------|----------|-----------|--------|----------|
| CH2436CH | 60cm x 90cm | 2' x 3' | 9.5mm | 2.1kg | Charcoal |
| СН3660СН | 90cm x 150cm | 3' x 5' | 9.5mm | 4.3kg | Charcoal |
| CH4872CH | 120cm x 180cm | 4' x 6' | 9.5mm | 6.4kg | Charcoal |

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

Get in touch

+44 (0) 1779 841 899 sales@bluediamond.uk.com www.bluediamond.uk.com



Chevron

| Technical Specification | | | | |
|-------------------------|--|--|--|--|
| Wear resistant: | Excellent wear resistance to level 3, suitable for heavy footfall | | | |
| Water absorbent: | Great water absorbency to level 2 | | | |
| Crush resistant: | Great crush resistance to level 2 | | | |
| Soil resistant: | Excellent resistance to soiling and stains to level 3 | | | |
| Disability friendly: | Yes, the low profile makes it suitable for wheelchair users | | | |
| Dry area: | Yes | | | |
| Environment: | Suitable for indoor use | | | |
| Flame retardant: | Yes | | | |
| Impact resistant: | Yes | | | |
| Product testing: | Classification of burning behaviour according to EN 13501-1:2007+ A1:2009 Test methods: Ignitability of products subjected to direct impingement of flame (ISO 11925-2:2010/C1:2011) and determination of the burning behaviour using a radiant heat source (ISO 9239-1:2010) | | | |
| Sustainability: | REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) | | | |
| Cleaning: | Vacuum, extraction clean, or can be hosed off | | | |