

Cushion Link Solid Top - General Purpose

Cushion Link Solid Top is a modular anti-fatigue matting system designed for various applications. Its textured surface provides the ultimate anti-slip protection while offering outstanding ergonomic comfort and safety. Ideal for heavy-duty or dry industrial areas, as well as gymnasiums, weight training areas, and other sporting venues due to their shock absorbing nature and noise reduction benefits. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - General Purpose contains 25% nitrile, making the product resistant to extreme temperatures. The adaptable solid top design is also compatible with the Cushion Link Open Top range.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape. The unique interlocking mechanism, along with male and female edges and bevels, provides secure connectivity.

Features

- Typical applications: Perfect for industrial and manufacturing areas as well gymnasiums, weight training areas plus other sporting venues.
- Material: Natural rubber, recycled rubber and nitrile rubber.
- Cleaning: Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- Sustainability: Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.

























Black only. Bevels

and yellow

available in both black

Code	Metric	Imperial	Thickness	Weight	Туре	Colour
CLS36GP	92cm x 92cm	3' x 3'	19mm	10.2kg	Mat	Black
CLS36BBF	92cm x 5.5cm	3' x 2"	19mm	0.75kg	Bevel - Female	Black
CLS36BBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Black
CLS36YBF	92cm x 5.5cm	3' x 2''	19mm	0.75kg	Bevel - Female	Yellow
CLS36YBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Yellow

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Cushion Link Solid Top - General Purpose

Technical Specification					
Slip resistant:	Excellent slip resistance to level 3. Our abrasive product is recommended for extremely slippery areas (slip resistant to R13 according to DIN51130)				
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Chemical resistant:	Yes, limited resistance to chemicals, oils and coolants				
Connectable:	Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides				
Cut to size:	Yes, mat can be cut to bespoke sizes				
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users				
Dry area:	Yes				
Heavy area:	Yes				
Wheeled area:	Yes				
Environment:	Suitable for indoor and outdoor use				
Flame retardant:	No, however, our nitrile and abrasive products have flame retardant properties				
Impact resistant:	Yes				
Product testing:	 Tensile strength: 3-3.5 Mpa Hardness: 55+ Shore A DIN abrasion loss mm³: 250-300 Elongation at break: 200-250% 				
Sustainability:	 Nature friendly, biodegradable and recyclable REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals 				
Temperature resistance:	-20°C to +130°C				
Cleaning:	Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended				