



Cushion Link Solid Top - Static Dissipative

Cushion Link Solid Top is a modular anti-fatigue matting system. The textured surface provides outstanding ergonomic comfort and safety in heavy duty dry ESD required areas. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - Static Dissipative has been designed to meet IEC61340-4-1 standard, measured resistance $R_g 10^6 - 10^9 \Omega$, $R_p 10^6 - 10^9 \Omega$.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape, whilst the unique interlocking mechanism along with male and female edges and bevels, provide secure connectivity.

Optional accessory available - Common Grounding Point Cord – Socket.

Features

- ◆ **Typical applications:** Perfect for electrostatically sensitive environments such as cleanrooms and electronic equipment assembly lines.
- ◆ **Material:** Static dissipative natural rubber.
- ◆ **Cleaning:** Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH and RoHS compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Black only. Bevels available in both black and yellow



For more information about this product or, to place an order [click here](#)



| Code | Metric | Imperial | Thickness | Weight | Type | Colour |
|----------|--------------|----------|-----------|--------|----------------|--------|
| CLS36SGP | 92cm x 92cm | 3' x 3' | 19mm | 12.7kg | Mat | Black |
| CLS36BBF | 92cm x 5.5cm | 3' x 2" | 19mm | 0.75kg | Bevel - Female | Black |
| CLS36BBM | 92cm x 5.5cm | 3' x 2" | 19mm | 0.90kg | Bevel - Male | Black |
| CLS36YBF | 92cm x 5.5cm | 3' x 2" | 19mm | 0.75kg | Bevel - Female | Yellow |
| CLS36YBM | 92cm x 5.5cm | 3' x 2" | 19mm | 0.90kg | Bevel - Male | Yellow |

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time.
That's the Blue Diamond difference.

V5.12.23

Get in touch

+44 (0) 1779 841 899
sales@bluediamond.uk.com
www.bluediamond.uk.com

Cushion Link Solid Top - Static Dissipative

Technical Specification

| | |
|-------------------------|---|
| Slip resistant: | Excellent slip resistant to level 3 |
| Anti-fatigue: | Excellent anti-fatigue properties, resistant to level 3 |
| Wear resistant: | Excellent wear resistance to level 3, suitable for heavy footfall |
| Chemical resistant: | Yes, limited resistance to chemicals, oils and coolants |
| Connectable: | Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides |
| Cut to size: | Yes, mat can be cut to bespoke sizes |
| Disability friendly: | Yes, the mats have ramped edges making them suitable for wheelchair users |
| Dry area: | Yes |
| Heavy area: | Yes |
| Wheeled area: | Yes |
| Environment: | Suitable for indoor use |
| Flame retardant: | No, however, our nitrile and abrasive products have flame retardant properties |
| Impact resistant: | Yes |
| Non-static (ESD): | ESD Rg = Rg $10^6 - 10^9 \Omega$ / ESD Rp = Rp $10^6 - 10^9 \Omega$ |
| Product testing: | <ul style="list-style-type: none"> ◆ Tensile strength: 3-3.5 Mpa ◆ Hardness: 55+ Shore A ◆ DIN abrasion loss mm³: 250-300 ◆ Elongation at break: 200-250% |
| Sustainability: | <ul style="list-style-type: none"> ◆ Recyclable material ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) ◆ RoHS (Restriction of Hazardous Substances) ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals |
| Temperature resistance: | -20°C to +130°C |
| Cleaning: | Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended |