

Diamond Grip Tape - Hazard

Diamond Grip - Hazard is an extremely tough, durable self-adhesive anti-slip tape with hazard chevrons for added protection for medium to high traffic areas. Along with possessing exceptional grip levels, the safetygrip is waterproof, can sustain most chemicals and, be used inside or out for added protection on steps or walkways.

Features

- Typical applications: Perfect for industrial and construction sites, commercial premises, universities, public buildings, residential, retail, sports facilities and offices.
- Material: Aluminium Oxide (80 grit) with solvent acrylic adhesive.
- Cleaning: Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water.
- Sustainability: REACH compliant.
- Warranty: Lifetime.





For more information about this product or, to place an order click here













Code	Metric	Imperial	Thickness	Weight	Туре	Colour
DGHZ01BY	25mm x 18.3m	1" x 60'	0.8mm	0.4kg	Roll	Black/Yellow
DGHZ02BY	50mm x 18.3m	2" x 60'	0.8mm	0.7kg	Roll	Black/Yellow
DGHZ04BY	100mm x 18.3m	4" x 60'	0.8mm	1.4kg	Roll	Black/Yellow
DGHZ06BY	150mm x 18.3m	6" x 60'	0.8mm	2kg	Roll	Black/Yellow
DGHZ624BY	610mm x 150mm	2' x 6"	0.8mm	0.08kg	Cleat	Black/Yellow

Please note, the thickness can be +/- 0.2mm

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Diamond Grip Tape - Hazard

Technical Specification					
Slip resistant:	Exceptional slip resistance to level 3				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Water absorbent:	Great water absorbency to level 2				
Crush resistant:	Great crush resistance to level 2				
Adhesion:	5.5kg / 25mm				
Application temperature:	10°C - 50°C				
Chemical resistant:	Yes, resistant to most chemicals, grease and oils				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Wet area:	Yes				
Wheeled area:	Due to the heavy-duty design, the tape can be crossed by trolleys and light weight machinery				
Environment:	Suitable for indoor and outdoor use				
Product testing:	 Slip resistant tested to DIN 51130: 2014 - class R13 Tensile strength: 12kgF / 25mm Elongation: 5% 				
Sustainability:	REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)				
Temperature resistance:	-30°C to +70°C				
UV resistant:	Yes				
Cleaning:	Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water				