



Diamond Interlock

Diamond Interlock is a heavy duty, interlocking rubber mat designed for quick and easy on-site installation in dry industrial environments. The mats are available as centre or end pieces for continuous lengths with bevelled edges to all sides for added safety. Along with being a very tough and durable mat, the moulded air pockets to the underside provide extra traction and ergonomic benefits.

Features

- ◆ **Typical applications:** Suitable for workshops, production lines, assembly areas and picking and packing stations.
- ◆ **Material:** Natural and recycled rubber.
- ◆ **Cleaning:** Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Black only



Suitable for indoor use



For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
DC2831	71cm x 78cm	2' x 3'	14mm	4.3kg	Centre tile	Black
DE2831	71cm x 78cm	2' x 3'	14mm	4.3kg	End tile	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time.
That's the Blue Diamond difference.

V4.02.24

Get in touch

+44 (0) 1779 841 899
sales@bluediamond.uk.com
www.bluediamond.uk.com

Diamond Interlock

Technical Specification

Slip resistant:	Great slip resistance to level 2
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3
Wear resistant:	Great wear resistance to level 2, suitable for medium to high footfall
Connectable:	Yes, the mats are modular and interlocking
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users
Dry area:	Yes
Wheeled area:	Yes, suitable for use by wheeled trolleys
Environment:	Suitable for indoor use
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none">◆ Tensile strength: 3-3.5 Mpa◆ Hardness: 55+ Shore A◆ DIN abrasion loss mm³: 200 - 250%◆ Elongation at break: 200-250%
Sustainability:	<ul style="list-style-type: none">◆ Nature friendly, biodegradable and recyclable◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals
Temperature resistance:	-20°C to +130°C
Cleaning:	Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended