


Interlocking Gym Mat

Our interlocking gym mat is an extremely durable, loose-lay interlocking floor tile perfect for comfort and safety in gymnasiums and weight training areas. The flat, textured surface allows for great stability whilst the bevel edges eliminate trip hazards. Made from 100% rubber, our heavy duty mat protects equipment from damage, absorbs shock, and reduces noise levels. The modular format, consisting of centre, corner and edge tiles, means the mat can be fitted into any area, size or shape and can be easily relocated if needed.

Features

- Typical applications: Perfect for gymnasiums and weight training areas plus ice skating arenas and other sporting venues.
- Material: Natural and recycled rubber.
- Cleaning: Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- Sustainability: Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.






















For more information about this product or, to place an order click here

Code	Metric	Imperial	Thickness	Weight	Туре	Colour
GT2424	60cm x 60cm	2' x 2'	10mm	5kg	Centre tile	Black
GTC2424	60cm x 60cm	2' x 2'	10mm	5kg	Corner tile	Black
GTE2424	60cm x 60cm	2' x 2'	10mm	5kg	Edge tile	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Interlocking Gym Mat

Technical Specification					
Slip resistant:	Great slip resistance to level 2				
Anti-fatigue:	Good anti-fatigue properties, resistant to level 1				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Connectable:	Yes, mats are connectable to create any shape or size				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Heavy area:	Yes				
Environment:	Suitable for indoor use				
Impact resistant:	Yes				
Product testing:	 Tensile strength: 3-3.5 Mpa Hardness: 55+ Shore A DIN abrasion loss mm³: 250-300 Elongation at break: 200-250% Minimum resistance to salt water and oil 				
Sustainability:	 Nature friendly, biodegradable and recyclable REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals 				
Temperature resistance:	-20°C to +130°C				
Cleaning:	Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended				