

Cushion Link Open Top - 100% Nitrile

Cushion Link Open Top is a modular anti-fatigue matting system. This ultimate matting provides outstanding ergonomic comfort and safety in heavy duty dry or wet industrial areas and catering kitchens. Manufactured from the highest quality resilient rubber compounds, Cushion Link Open Top - 100% Nitrile is resistant to extreme temperatures, oils, coolants, and most chemicals. The adaptable open top design provides excellent drainage and swarf removal leaving the floor surface dry, clean, and safe.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape, whilst the unique interlocking mechanism along with male and female edges and bevels, provide secure connectivity. This product is also compatible with our Cushion Link Solid Top range.

Features

- ◆ **Typical applications:** Perfect for oily, greasy, welding and manufacturing areas. Also ideal for kitchens and catering facilities.
- ◆ **Material:** Nitrile rubber.
- ◆ **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.

Suitable for indoor and outdoor use



For more information about this product or, to place an order [click here](#)



Black only. Bevels available in both black and yellow



| Code | Metric | Imperial | Thickness | Weight | Type | Colour |
|----------|--------------|----------|-----------|--------|----------------|--------|
| CLO36NFR | 92cm x 92cm | 3' x 3' | 19mm | 9kg | Mat | Black |
| CLS36BBF | 92cm x 5.5cm | 3' x 2" | 19mm | 0.75kg | Bevel - Female | Black |
| CLS36BBM | 92cm x 5.5cm | 3' x 2" | 19mm | 0.90kg | Bevel - Male | Black |
| CLS36YBF | 92cm x 5.5cm | 3' x 2" | 19mm | 0.75kg | Bevel - Female | Yellow |
| CLS36YBM | 92cm x 5.5cm | 3' x 2" | 19mm | 0.90kg | Bevel - Male | Yellow |

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

V5.02.24

Get in touch

+44 (0) 1779 841 899
sales@bluediamond.uk.com
www.bluediamond.uk.com

Cushion Link Open Top - 100% Nitrile

Technical Specification

| | |
|-------------------------|---|
| Slip resistant: | Excellent slip resistance to level 3 |
| Anti-fatigue: | Excellent anti-fatigue properties, resistant to level 3 |
| Wear resistant: | Excellent wear resistance to level 3, suitable for heavy footfall |
| Water absorbent: | The design allows liquids to self-drain |
| Chemical resistant: | Yes |
| Connectable: | Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides |
| Cut to size: | Yes, mat can be cut to bespoke sizes |
| Disability friendly: | Yes, the mats have ramped edges making them suitable for wheelchair users |
| Dry area: | Yes |
| Wet area: | Yes |
| Oily and greasy area: | Yes |
| Heavy area: | Yes |
| Welding area: | Yes |
| Wheeled area: | Yes |
| Environment: | Suitable for indoor and outdoor use |
| Flame retardant: | Yes |
| Impact resistant: | Yes |
| Product testing: | <ul style="list-style-type: none"> ◆ Tensile strength: 3-3.5 Mpa ◆ Hardness: 55+ Shore A ◆ DIN abrasion loss mm³: 250-300 ◆ Elongation at break: 200-250% ◆ Fire tested to: BS EN 13501-1 Class Efl – S2 |
| Sustainability: | <ul style="list-style-type: none"> ◆ Nature friendly, biodegradable and recyclable ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals |
| Temperature resistance: | -20°C to +130°C |
| Cleaning: | Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended |