

Cushion Link Solid Top - 100% Nitrile

Cushion Link Solid Top is a modular anti-fatique matting system. The textured surface provides outstanding ergonomic comfort and safety in heavy duty dry or wet industrial areas. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - 100% Nitrile is resistant to extreme temperatures, oils, coolants and most chemicals. The adaptable solid top design is also compatible with our Cushion Link Open Top range.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape, whilst the unique interlocking mechanism along with male and female edges and bevels, provide secure connectivity. This product is also compatible with our Cushion Link Open Top range.

Features

- Typical applications: Perfect for oily, greasy, welding and manufacturing areas.
- Material: Nitrile rubber.
- Cleaning: Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- Sustainability: Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.



Black only. Bevels available in both black and yellow



















For more information about this product or, to place an order click here



Code	Metric	Imperial	Thickness	Weight	Туре	Colour
CLS36NFR	92cm x 92cm	3' x 3'	19mm	10.2kg	Mat	Black
CLS36BBF	92cm x 5.5cm	3' x 2"	19mm	0.75kg	Bevel - Female	Black
CLS36BBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Black
CLS36YBF	92cm x 5.5cm	3' x 2"	19mm	0.75kg	Bevel - Female	Yellow
CLS36YBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Yellow

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Cushion Link Solid Top - 100% Nitrile

Technical Specification					
Slip resistant:	Excellent slip resistance to level 3. Our abrasive product is recommended for extremely slippery areas (slip resistant to R13 according to DIN51130)				
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Chemical resistant:	Yes				
Connectable:	Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides				
Cut to size:	Yes, mat can be cut to bespoke sizes				
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users				
Dry area:	Yes				
Oily and greasy area:	Yes				
Heavy area:	Yes				
Welding area:	Yes				
Wheeled area:	Yes				
Environment:	Suitable for indoor and outdoor use				
Flame retardant:	Yes				
Impact resistant:	Yes				
Product testing:	 Tensile strength: 3-3.5 Mpa Hardness: 55+ Shore A DIN abrasion loss mm³: 250-300 Elongation at break: 200-250% Fire tested to: BS EN 13501-1 Class Efl – S2 				
Sustainability:	 Nature friendly, biodegradable and recyclable REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals 				
Temperature resistance:	-20°C to +130°C				
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended				