

Cushion Link Solid Top - General Purpose

Cushion Link Solid Top is a modular anti-fatigue matting system designed for various applications, particularly suited for heavy-duty, manufacturing or dry industrial areas. Its textured surface provides the ultimate anti-slip protection while offering outstanding ergonomic comfort and safety. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - General Purpose contains 25% nitrile, making the product resistant to extreme temperatures. The adaptable solid top design is also compatible with the Cushion Link Open Top range.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape. The unique interlocking mechanism, along with male and female edges and bevels, provides secure connectivity.

Features

- Typical applications: Perfect for industrial and manufacturing areas.
- Material: Natural rubber, recycled rubber and nitrile rubber.
- Cleaning: Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- Sustainability: Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.

















	113					
For mor	e inform	ation abo	ut this p	roduct or	, to place an	order click here

Code	Metric	Imperial	Thickness	Weight	Туре	Colour
CLS36GP	92cm x 92cm	3' x 3'	19mm	10.2kg	Mat	Black
CLS36BBF	92cm x 5.5cm	3' x 2''	19mm	0.75kg	Bevel - Female	Black
CLS36BBM	92cm x 5.5cm	3' x 2''	19mm	0.90kg	Bevel - Male	Black
CLS36YBF	92cm x 5.5cm	3' x 2''	19mm	0.75kg	Bevel - Female	Yellow
CLS36YBM	92cm x 5.5cm	3' x 2''	19mm	0.90kg	Bevel - Male	Yellow

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Cushion Link Solid Top - General Purpose

Technical Specification	Technical Specification					
Slip resistant:	Excellent slip resistance to level 3. Our abrasive product is recommended for extremely slippery areas (slip resistant to R13 according to DIN51130)					
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3					
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall					
Chemical resistant:	Yes, limited resistance to chemicals, oils and coolants					
Connectable:	Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides					
Cut to size:	Yes, mat can be cut to bespoke sizes					
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users					
Dry area:	Yes					
Heavy area:	Yes					
Wheeled area:	Yes					
Environment:	Suitable for indoor and outdoor use					
Flame retardant:	No, however, our nitrile and abrasive products have flame retardant properties					
Impact resistant:	Yes					
Product testing:	 Tensile strength: 3-3.5 Mpa Hardness: 55+ Shore A DIN abrasion loss mm³: 250-300 Elongation at break: 200-250% 					
Sustainability:	 Nature friendly, biodegradable and recyclable REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals 					
Temperature resistance:	-20°C to +130°C					
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended					