

Diamond Grip Tape - General Purpose

Diamond Grip - General Purpose is a tough, durable self-adhesive anti-slip tape perfect for medium to high traffic areas. Along with possessing excellent grip levels, the safety-grip is waterproof, can sustain most chemicals and, can be used inside or out for added protection on steps or walkways.

Features

- Typical applications: Perfect for industrial and construction sites, commercial premises, universities, public buildings, residential, retail, sports facilities and offices.
- Material: Aluminium Oxide (80 grit) with solvent acrylic adhesive.
- Cleaning: Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water.
- Sustainability: REACH compliant.
- Warranty: Lifetime.

Suitable for

























Code	Metric	Imperial	Thickness	Weight	Туре	Colour
DGGP01BL	25mm x 18.3m	1" x 60'	0.8mm	0.4kg	Roll	Black
DGGP01YL	25mm x 18.3m	1" x 60'	0.8mm	0.4kg	Roll	Yellow
DGGP02BL	50mm x 18.3m	2" x 60'	0.8mm	0.7kg	Roll	Black
DGGP02YL	50mm x 18.3m	2" x 60'	0.8mm	0.7kg	Roll	Yellow
DGGP04BL	100mm x 18.3m	4" x 60'	0.8mm	1.5kg	Roll	Black
DGGP04YL	100mm x 18.3m	4" x 60'	0.8mm	1.5kg	Roll	Yellow
DGGP06BL	150mm x 18.3m	6" x 60'	0.8mm	2kg	Roll	Black
DGGP06YL	150mm x 18.3m	6" x 60'	0.8mm	2kg	Roll	Yellow
DGGP624BL	610mm x 150mm	2' x 6"	0.8mm	0.08kg	Cleat	Black

Please note, the thickness can be +/- 0.2mm

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



Diamond Grip Tape - General Purpose

Technical Specification					
Slip resistant:	Excellent slip resistance to level 3				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Water absorbent:	Great water absorbency to level 2				
Crush resistant:	Great crush resistance to level 2				
Adhesion:	5.5kg / 25mm				
Application temperature:	10°C - 50°C				
Chemical resistant:	Yes, resistant to most chemicals, grease and oils				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Wet area:	Yes				
Wheeled area:	Due to the heavy-duty design, the tape can be crossed by trolleys and light weight machinery				
Environment:	Suitable for indoor and outdoor use				
Product testing:	 Slip resistant tested to DIN 51130: 2014 - class R13 Tensile strength: 12kgF / 25mm Elongation: 5% 				
Sustainability:	REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)				
Temperature resistance:	-20°C to +65°C				
UV resistant:	Yes				
Cleaning:	Dirt and debris can easily be removed using a stiff brush. Where dirt has become embedded, or to remove spillages, we recommend using a detergent and warm water				