



# Diamond Interlock

Diamond Interlock is a heavy duty, interlocking rubber mat designed for quick and easy on-site installation in dry industrial environments. The mats are available as centre or end pieces for continuous lengths with bevelled edges to all sides for added safety. Along with being a very tough and durable mat, the moulded air pockets to the underside provide extra traction and ergonomic benefits.

## Features

- ◆ **Typical applications:** Suitable for workshops, production lines, assembly areas and picking and packing stations.
- ◆ **Material:** Natural and recycled rubber.
- ◆ **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.

Suitable for indoor use



For more information about this product or, to place an order [click here](#)



Black only



Code	Metric	Imperial	Thickness	Weight	Type	Colour
DC2831	71cm x 78cm	2' x 3'	14mm	4.3kg	Centre tile	Black
DE2831	71cm x 78cm	2' x 3'	14mm	4.3kg	End tile	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

## Our delivery promise

We guarantee your order will be shipped on time, every time.  
That's the Blue Diamond difference.

V4.02.24

## Get in touch

+44 (0) 1779 841 899  
sales@bluediamond.uk.com  
www.bluediamond.uk.com

# Diamond Interlock

## Technical Specification

Slip resistant:	Great slip resistance to level 2
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3
Wear resistant:	Great wear resistance to level 2, suitable for medium to high footfall
Connectable:	Yes, the mats are modular and interlocking
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users
Dry area:	Yes
Wheeled area:	Yes, suitable for use by wheeled trolleys
Environment:	Suitable for indoor use
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none"><li>◆ Tensile strength: 3-3.5 Mpa</li><li>◆ Hardness: 55+ Shore A</li><li>◆ DIN abrasion loss mm<sup>3</sup>: 200 - 250%</li><li>◆ Elongation at break: 200-250%</li></ul>
Sustainability:	<ul style="list-style-type: none"><li>◆ Nature friendly, biodegradable and recyclable</li><li>◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)</li><li>◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals</li></ul>
Temperature resistance:	-20°C to +130°C
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended