

# Ergotred

Ergotred is a versatile anti-fatigue loose lay mat which is manufactured from heavy duty flexible rubber known for its 5-star comfort rating. The domed air cushioned pockets across the surface have been designed to provide optimal worker comfort and improve circulation. The bevelled yellow edges and suction cup backing enhance the anti-slip properties, making it an ideal mat for heavy duty dry industrial and manufacturing environments and many more applications.

### Features

- Typical applications: In addition to industrial and manufacturing environments, Ergotred is perfect for storage facilities, workshops, warehouses, security guard rooms, commercial offices, kennels, livery enclosures and dog grooming areas due to its durability.
- Material: Natural rubber.
- Cleaning: Use a vacuum cleaner, hose down, or wash with mild detergents. The use of harsh detergents is not recommended.
- Sustainability: Recyclable material. REACH compliant.



Warranty: Lifetime.



For more information about this product or, to place an order **click here** 

Code	Metric	Imperial	Thickness	Weight	Colour
ER2436	60cm x 90cm	2' x 3'	14.5mm	3.7kg	Black/Yellow
ER3648	90cm x 120cm	3' x 4'	14.5mm	10.4kg	Black/Yellow

Please note, the thickness can be +/- 0.5mm

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

## Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

### Get in touch

+44 (0) 1779 841 899 sales@bluediamond.uk.com www.bluediamond.uk.com



# **Ergotred**

Technical Specification				
Slip resistant:	Excellent slip resistance to level 3			
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3. Ergotred also improves circulation			
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall			
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users			
Dry area:	Yes			
Environment:	Suitable for indoor use			
Product testing:	Slip Resistance R 10 according to DIN 51130:2014			
Sustainability:	<ul> <li>Recyclable material</li> <li>REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)</li> </ul>			
Temperature resistance:	-30°C to +50°C			
Cleaning:	Use a vacuum cleaner, hose down, or wash with mild detergents. The use of harsh detergents is not recommended			