

LogoScrape

LogoScrape delivers superior scraping action to effectively remove dirt and debris, making it a practical solution for both indoor and outdoor environments. It is available with two backing options: solid rubber for indoor use and a version with integrated drainage holes for outdoor applications, allowing water to self-drain and helping to maintain a safer, drier surface.

Built for durability, LogoScrape features a compression-moulded rubber backing with reinforced borders on all four sides, ensuring long-lasting performance even in high-traffic areas.

The surface is made from 100% ECONYL® regenerated nylon derived from waste products, and the rubber backing contains 34% post-industrial recycled content, combining strength with sustainability.

Logo mats are the perfect platform to showcase your company logo or message. With LogoScrape, you have a customisable solution that works for both indoor and outdoor use. Choose from over 50 colours to create a design that reflects your brand.

To order, decide on your mat size and whether your mat is for indoor or outdoor use, email a high-resolution image of your design and brand guidelines to sales@bluediamond.uk.com in PDF, JPEG, or similar file format. Once your order is confirmed, you'll receive a full-colour proof for approval.

Please note: The maximum size for LogoScrape with drainage holes is 115cm x 200cm. The size of the holes are 7mm in diameter.

Features

- Typical applications: Perfect for indoor and outdoor use in schools, universities, public buildings, sports facilities, shopping malls, offices, hotels and bars, and restaurants.
- Material: 100% ECONYL® regenerated nylon surface derived from waste products, with 100% nitrile backing containing 34% post-industrial recycled content.
- **Cleaning**: Use a vacuum cleaner or an extraction cleaner to remove dirt. LogoScrape is also machine washable.

































For more information about this product or, to place an order click here

Code	Metric	Imperial	Thickness	Weight	Туре
LS2436	60cm x 85cm	2' x 3'	10mm	1.7kg	Indoor
LS3648	85cm x 115cm	3' × 4'	10mm	2.7kg	Indoor





Code	Metric	Imperial	Thickness	Weight	Туре
LS3660	85cm x 150cm	3' x 5'	10mm	3.4kg	Indoor
LS310	85cm x 300cm	3' x 10'	10mm	6.9kg	Indoor
LS4872	115cm x 180cm	4' x 6'	10mm	5.8kg	Indoor
LS4879	115cm x 200cm	4' x 7'	10mm	5.8kg	Indoor
LS4896	115cm x 240cm	4' x 8'	10mm	7.1kg	Indoor
LS5979	150cm x 200cm	5' x 7'	10mm	7.95kg	Indoor
LS5998	150cm x 250cm	5' x 8'	10mm	8.9kg	Indoor
LS5910	150cm x 300cm	5' x 10'	10mm	11.9kg	Indoor
LS7910	200cm x 300cm	7' x 10'	10mm	15.9kg	Indoor
LSO2436	60cm x 85cm	2' x 3'	10mm	1.7kg	Outdoor
LSO3648	85cm x 115cm	3' x 4'	10mm	2.7kg	Outdoor
LSO3660	85cm x 150cm	3' x 5'	10mm	3.4kg	Outdoor
LSO4872	115cm x 180cm	4' x 6'	10mm	5.8kg	Outdoor
LSO4879	115cm x 200cm	4' x 7'	10mm	5.8kg	Outdoor

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number Please note, the maximum size for LogoScrape with drainage holes is $115 \, \text{cm} \times 200 \, \text{cm}$

Technical Specification					
Slip resistant:	Great slip resistance to level 2				
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall				
Water absorbent:	3.160kg/m² absorbancy. When used externally, drainage holes allow water to self-drain				
Crush resistant:	Great crush resistance to level 2				
Soil resistant:	Excellent resistance to soiling and stains to level 3				
Chemical resistant:	Yes, maximum oil resistance				
Cut to length:	Bespoke sizes available on request				
Cut to size:	Bespoke sizes available on request				





Technical Specification					
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Wet area:	Yes				
Oily and greasy area:	Yes				
Heavy area:	Yes				
Environment:	Suitable for indoor and outdoor use				
Flame retardant:	Yes				
Product testing:	 Static Electrical Propensity – Walking Test: 0.3 kV (ISO 6356) Dynamic Coefficient of Friction: 0.50 DS (EN 13893) Flammability: Classified Dfl-s1 (EN 13501-1) 				
Sustainability:	 Surface is made from 100% ECONYL® regenerated nylon derived from waste products 100% nitrile backing contains 34% post-industrial recycled content 				
Cleaning:	Use a vacuum cleaner or an extraction cleaner. LogoScrape is also machine washable				
Machine washable:	Maximum 40-50°C - Mat can also be tumble dried. Due to its abrasive pile, LogoScrape may attract lint if washed with other mat types. For best results, wash separately. If mixed washing is unavoidable, tumble-dry to reduce linting. After drying, lay mats flat to cool before rolling. Avoid storing damp mats folded or stacked to prevent colour transfer				

ECONYL®

The ECONYL® regeneration process gives a new life to waste materials that would otherwise be sent to landfill, transforming them into a new source of opportunities, in this case LogoScrape.

Nylon waste – such as fishing nets, fabric scraps, carpet flooring, and industrial plastic – is recovered and converted into new yarn, which has the same qualitative characteristics as traditional nylon.

In the Life Cycle assessment of the nylon value chain, they discovered that the highest negative impact on our planet came from the raw material extraction phase.

Years and years of research finally led to the development of the ECONYL® Regeneration System: a highly innovative industrial process that allows replacing caprolactam (the main component to produce Nylon 6, derived from oil) with alternative raw materials coming from the recycling of various types of nylon waste.



LogoScrape (LogoScrape)

Colour Chart

A1	B1	C1	Dì	ΕΊ	
A2	B2	C2	D2	E2	
A3	В3	C3	D3	E3	
A4	В4	C4	D4	E4	
A5	B5	C5	D5	E5	
A6	В6	C6	D6	E6	
A7	В7	C7	D7	E7	
A8	В8	C8	D8	E8	
A9	В9	C9	D9	E9	
A10	B10	C10	D10	E10	