

# Plate Finish Rubber

Plate Finish Rubber is a general purpose smooth rubber used for a wide variety of applications, such as gaskets and waterproof seals. Available in two different thicknesses, 3mm and 6mm, Plate Finish Rubber can be supplied as rolls or cut to length for that perfect fit.

## Features

- ◆ **Typical applications:** Ideal for waterproof seals and gaskets, workbench protective coverings, flooring, vehicle interiors and drawer and shelf liners.
- ◆ **Material:** 100% rubber.
- ◆ **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- ◆ **Sustainability:** REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Suitable for indoor use



For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
PR3140	140cm x 10m	5' x 33'	3mm	61kg	Roll	Black
PR6140	140cm x 10m	5' x 33'	6mm	116kg	Roll	Black
PR3140C	140cm wide	5' wide	3mm	6.1kg	Cut length - per m	Black
PR6140C	140cm wide	5' wide	6mm	11.6kg	Cut length - per m	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

## Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

V5.02.24

## Get in touch

+44 (0) 1779 841 899  
[sales@bluediamond.uk.com](mailto:sales@bluediamond.uk.com)  
[www.bluediamond.uk.com](http://www.bluediamond.uk.com)

# Plate Finish Rubber

## Technical Specification

Wear resistant: Excellent wear resistance to level 3, suitable for heavy footfall

Cut to length: Yes, the rubber can be cut to length

Cut to size: Yes, the rubber can be cut to bespoke sizes

Dry area: Yes

Wheeled area: Yes

Environment: Suitable for indoor use

Impact resistant: Yes

Product testing:

- ◆ Hardness Shore A  $\pm 5$  65° ISO 7619-1
- ◆ SG (g/cm<sup>2</sup>) 1.50 ISO 2781
- ◆ Tensile (N/mm<sup>2</sup>) 3 ISO 37
- ◆ Elongation % 250 ISO 37
- ◆ Compression % 43 ISO 37
- ◆ Tear Strength 10.5 ISO 34-1
- ◆ Abrasion mm<sup>3</sup> ISO 37

Sustainability:

- ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)
- ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals

Temperature resistance: -20°C to +70°C

Cleaning:

Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended